



“GET STIPPLED”

Shop Address:
84/86 Industry Drive
Tweed Heads South,
NSW 2486

Postal Address:
P.O. Box 351,
Banora Point,
N.S.W. 2486

Phone:
+61 7 55244 235 or
+61 7 55233 539

Fax:
+61 7 5524 6940

Web: www.getstippled.com
E-Mail: info@getstippled.com



INTERIOR/ EXTERIOR WALL AND CEILING TEXTURE COATINGS

ULTRATEX MATERIAL SAFETY SHEET 1

THIS MATERIAL TESTED BY THE CSIRO AND COMPLIES WITH ASINZS 1530.3:1999.

WE GUARANTEE OUR PRODUCTS WHEN USED IN ACCORDANCE WITH OUR COMPLETE SYSTEM AND APPLIED USING THE BEST ACCEPTED TRADE PRACTICES.

OTHER NAMES:

Trowel/roll-on texture coatings (Water Based).

USES:

Texture coating for wall and ceilings of homes and buildings. Normally applied manually by trowel or roller.

PHYSICAL DESCRIPTION/PROPERTIES:

Appearance:	Thick white or coloured liquid.
Boiling Point:	100c (water is solvent).
Melting Point:	0c (water is solvent).
Vapour Pressure:	17mm Hg @ 20 Degrees Celsius.
Specific Gravity:	1.75 to 1.90.
Flash Point:	Non-combustible.
Flammability Uimits:	Not Applicable.
Solubility in Water:	Miscible with water.

OTHER PROPERTIES:

Auto-ignition Temperature:	Not Applicable.
Rel Vapour Density:	(Air = 1) < 1 Water.
Ph:	8 to 9.5.
% Volatile by Volume:	36 to 44.

INGREDIENTS:

CHEMICAL ENTITY	CAS NUMBER	PROPORTION %
Acrylic resin emulsion (propriety)	Not Known	15 - 35
Individual residual monomers	Not Required	< 0.1
Pigments (white, coloured, inert)	Mixture	20 - 30
Graded Sand	Mixture	35 - 50
Propylene Glycol	57-55-6	1 - 3
Coalescent Agent	25265-77-4	1 - 3
Aqua Ammonia	1336-21-6	< 0.2
Water	7732-18-5	Balance



"GET STIPPLED"

Shop Address:
84/86 Industry Drive
Tweed Heads South,
NSW 2486

Postal Address:
P.O. Box 351,
Banora Point,
N.S.W. 2486

Phone:
+61 7 55244 235 or
+61 7 55233 539

Fax:
+61 7 5524 6940

Web: www.getstippled.com
E-Mail: info@getstippled.com



INTERIOR/ EXTERIOR WALL AND CEILING TEXTURE COATINGS

ULTRATEX MATERIAL SAFETY SHEET 2

THIS MATERIAL TESTED BY THE CSIRO AND COMPLIES WITH ASINZS 1530.3:1999.

WE GUARANTEE OUR PRODUCTS WHEN USED IN ACCORDANCE WITH OUR COMPLETE SYSTEM AND APPLIED USING THE BEST ACCEPTED TRADE PRACTICES.

HEALTH HAZARD INFORMATION

HEALTH EFFECTS:

ACUTE:

Swallowed: None Allocated.
Eye: Direct contact with eye may cause slight irritation.
Skin: Prolonged or repeated skin contact may cause slight irritation.
Inhaled: Inhalation of the vapour or mist can cause irritation of the nose, throat and lungs, and could headache and nausea.
Chronic: None Allocated.

FIRST AID:

Swallowed: If swallowed give two glasses of water to drink. Consult a doctor. Never give anything by mouth to an unconscious person.
Eye: In case of contact with eyes, rinse immediately with plenty of water. Contact a doctor if irritation persists.
Skin: After contact with skin, wash thoroughly with soap and water. Consult a doctor if irritation persists.
Inhaled: Move affected person to a well-ventilated area where this product is used.
Advice to Doctor: Treat symptomatically.

PRECAUTIONS FOR USE:

EXPOSURE STANDARDS:

No exposure standard allocated.

ENGINEERING CONTROLS:

Good ventilation required. Ensure a minimum capture velocity of 0.5 m/sec at point of application – use local exhaust ventilation in confined areas when applying by spray methods. Refer to Australian Standards AS 1668.

PERSONAL PROTECTION:

Respiratory Protection (an Australian Standards) approved half-mask, air-purifying respirator (cartridge-ammonia/methylamine type) should be worn when applying by spray-gun. Whenever workplace conditions warrant, respiratory protection must conform with the requirements of AS1715 and AS1716.



"GET STIPPLED"

Shop Address:
84/86 Industry Drive
Tweed Heads South,
NSW 2486
Postal Address:
P.O. Box 351,
Banora Point,
N.S.W. 2486

Phone:
+61 7 55244 235 or
+61 7 55233 539
Fax:
+61 7 5524 6940

Web: www.getstippled.com
E-Mail: info@getstippled.com



INTERIOR/ EXTERIOR WALL AND CEILING TEXTURE COATINGS

ULTRATEX MATERIAL SAFETY SHEET 3 PAGE 1

THIS MATERIAL TESTED BY THE CSIRO AND COMPLIES WITH ASINZS 1530.3:1999.

WE GUARANTEE OUR PRODUCTS WHEN USED IN ACCORDANCE WITH OUR COMPLETE SYSTEM AND APPLIED USING THE BEST ACCEPTED TRADE PRACTICES.

HEALTH HAZARD INFORMATION

PRECAUTIONS FOR USE (continued)

EYE PROTECTION:

Eye protectors, goggles conforming to AS1337 recommended to prevent splashes entering eyes.

HAND PROTECTION:

Avoid unnecessary skin contact. Wear PVC or Neoprene chemically resistant gloves to prevent prolonged exposure and when handling large spills.

FLAMMABILITY:

Non-combustible.

SAFE HANDLING INFORMATION:

Storage and Transport.
Dangerous Goods Class.....: None Allocated.
Subsidiary Risk.....: None Allocated.

STORAGE CONDITIONS:

Store in a cool dry protected area. Recommended storage temperature is a minimum of 4c to a maximum of 45c.

TRANSPORT:

Not classified as dangerous goods. No special procedures required. No EPG (Emergency Procedure Guide required)

SPIILLS AND LEAK HANDLING INFORMATION:

Personal protection: Refer to PRECAUTIONS FOR USE information for recommended eye and hand protection measures.

FIRST AID:

If exposed during clean-up, refer HEALTH HAZARD Information section for recommended first aid.



"GET STIPPLED"

Shop Address:
84/86 Industry Drive
Tweed Heads South,
NSW 2486

Postal Address:
P.O. Box 351,
Banora Point,
N.S.W. 2486

Phone:
+61 7 55244 235 or
+61 7 55233 539

Fax:
+61 7 5524 6940

Web: www.getstippled.com
E-Mail: info@getstippled.com



INTERIOR/ EXTERIOR WALL AND CEILING TEXTURE COATINGS

ULTRATEX MATERIAL SAFETY SHEET 3 PAGE 2

THIS MATERIAL TESTED BY THE CSIRO AND COMPLIES WITH ASINZS 1530.3:1999.

WE GUARANTEE OUR PRODUCTS WHEN USED IN ACCORDANCE WITH OUR COMPLETE SYSTEM AND APPLIED USING THE BEST ACCEPTED TRADE PRACTICES.

continued from page 3.

RECOMMENDED CLEAN UP PROCEDURES:

Floor may be slippery, use care to prevent falling. Contain spills immediately with inert absorbent material (e.g. sand, earth). Transfer both spilled liquid and the solid absorbent material to suitable containers for recovery or disposal. Prevent material entering drains and/or watercourses.
Dispose of in accordance with local government regulations for the disposal of non-hazardous paint/acrylic render waste.

FIRE/EXPLOSION HAZARD:

Product may splatter at temperatures above 100c. Hot splattered paint can form films which can burn the skin.

EXTINGUISHING AGENTS:

Use extinguishing method appropriate to surrounding fire.

PERSONAL PROTECTIVE EQUIPMENT:

Wear self-contained breathing apparatus.

TOXICITY DATA:

No specific product toxicity data available.

NOTE:

The following is based upon toxicity profiles of typical polymer emulsions used in the paint and plastering industries and is believed to be representative of this product.
Oral LDSO rat: < 500mg/kg.
Eye Irritation rabbit (Inconsequential irritation).
Skin Irritation rabbit (Practically non-irritating).

NOTE: IF ANY MORE INFORMATION IS REQUIRED PLEASE CONTACT US A.S.A.P.
CONTACT POINT: MANAGER