



“GET STIPPLED”

Shop Address:
84/86 Industry Drive
Tweed Heads South,
NSW 2486

Postal Address:
P.O. Box 351,
Banora Point,
N.S.W. 2486

Phone:
+61 7 55244 235 or
+61 7 55233 539

Fax:
+61 7 5524 6940

Web: www.getstippled.com
E-Mail: info@getstippled.com



INTERIOR/ EXTERIOR WALL AND CEILING TEXTURE COATINGS

ULTRATEX SANDCOTE

THIS MATERIAL TESTED BY THE CSIRO AND COMPLIES WITH ASINZS 1530.3:1999.

WE GUARANTEE OUR PRODUCTS WHEN USED IN ACCORDANCE WITH OUR COMPLETE SYSTEM AND APPLIED USING THE BEST ACCEPTED TRADE PRACTICES.

DESCRIPTION:

A flexible polymer-based render, ready-for-use trowel-on coating. Relatively smooth finish giving the appearance of natural stone. Pre-mixed to colour in the factory to emulate the texture and appeal of old-style render and lime-washed coatings. Sandstone possesses those long-lasting acrylic performance characteristics that were nonexistent in the older Mediterranean or abode finishes, due to 'up-to-the-minute' acrylic technology employed in its manufacture.

USE ON:

Cement render, tilt-up concrete, AAC blocks and panels, off-form concrete, Harditex sheeting, blueboard, concrete blocks and clay bricks etc (refer to notes on skim-coats patching). Suitable for housing, commercial, high rise, blockwork/blueboard fences and any suitably prepared masonry surfaces.

COLOUR RANGE:

White base colours can be tinted.

PROPERTIES:

Profile:	Sandy fine
Surface:	Smooth, but fine grained
Dry film:	Varies, but each coat should build to a minimum of 1mm
Weather Resistance	Excellent (extended life when over-coated)
Solvent:	Water
Odour:	Low (Wet) nil (Dry)

SURFACE PREPARATION:

Refer notes on SUBSTRATES.

APPLICATION METHOD # 1:

1.Product is applied with a steel trowel and finished with a sponge float or plastic float to provide a smooth, cohesive, fine sand appearance.

NOTE;

FOR EXTRA PROTECTION USE ONE EXTRA COAT OF ULTRATEX PROTECT SATIN or ULTRATEX SUPAFLEX

PACKAGING:

ULTRATEX SANDCOTE is supplied in ready for use re-sealable 4ltr and 15ltr plastic containers.